



## Optileb™ GR UF Range

Food Grade Grease

### Description

Castrol Optileb™ GR UF Range (Previously called Obeen™ UF ) - are light, natural-colored special greases. They are physiologically safe and contain only components which are NSF H1 registered and comply with the U.S. Code of Federal Regulations, Title 21, Section 178.3570 and 178.3620 by the Food and Drug Administration (USA) as lubricants where incidental food contact may occur. The range of products under Optileb GR range are Kosher and Halal approved.

### Application

Optileb GR UF is especially suited for the use in the food and beverage industries as well as in the pharmaceutical industry where there may be exposure of the lubricated part to the edible product or its packaging.

Optileb GR UF 00 for grease-lubricated gears and gear motors - central lubrication systems such as in filling plants, packaging stations and cardboard folding machines.

Optileb GR UF 1, 2 as tap, sealing and bearing grease, for long term lubrication of rolling and sliding bearings, for fillers, bottle washing machines, labelling machines, closing machines, filling machines, conches, cyclones. Optileb GR UF 2 guarantees mobility of taps. Optileb GR UF 2 is available in aerosol cans. The aerosol cans don't have H1 approval.

### Advantages

- Physiologically safe.
- Odorless and tasteless
- Resistant to hot and cold water.
- Excellent conveying ability.
- Good anti-corrosion properties.
- Resists water wash out.

## Typical Characteristics

Name	Method	Units	GR UF 00	GR UF 1	GR UF 2
Colour	Visual	-	Whitish, Transparent	Whitish, Transparent	Whitish, Transparent
Consistency / NLGI Grade	DIN 51818	-	00	1	2
Base Oil	-	-	Synthetic Oil	Synthetic Oil	Synthetic Oil
Thickner Type	-	-	Aluminum Complex	Aluminum Complex	Aluminum Complex
Worked Penetration (60 strokes)	ASTM D 217 / ISO 2137	0.1 mm	420	320	280
Dropping Point	ASTM D566 / ISO 2176	°C / °F	195 / 381	>230 / 446	>230 / 446
Water Resistance at 90°C / 194°F	DIN 51807-1	Rating	-	0	0
Rust test - Emcor - distilled water	ASTM D6138 / ISO 11007	Rating	0/1	0/1	0/1
Copper corrosion (24 hrs @ 100°C/212°F )	ASTM D130 / ISO 2160	Rating	1b	1b	1b

These technical data are based on average test results. Minor deviations may occur from case to case.

## User Advice

- Please observe the machine manufacturers' lubrication specifications.
- Temperature application range:
  - Optileb GR UF 00 : -40°C/-40°F to +140°C/+284°F
  - Optileb GR UF 1, 2 : -30°C/-22°F to +140°C +284°F

**This product was previously called Obeen UF . The name was changed in 2015.**

Optileb™ GR UF Range

12 May 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 352, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0845 9645111 Technical Enquiries: 0845 9000209

[www.castrol.com/industrial](http://www.castrol.com/industrial)